

Features



- Excellent power handling
- small size
- Low loss
- temperature stable
- LTCC construction , and has good moisture resistance, corrosion resistance, high reliability.

Applications


- Harmonic Rejection
- VHF/UHF transmitters / receivers
- Base Station/Micro base station of Mobile Communication, Internet of things terminal, lab use.

Electrical Specifications at 25°C

Parameter		Frequency(MHz)	Min.	Typ.	Max.	Unit
Pass Band	Insertion Loss	DC-3000	-	1.1	2.2	dB
	Freq.Cut-Off	3460	-	3.0	-	dB
	Return Loss	DC-3000	-	18	-	dB
Stop Band	Rejection Loss	4550-4800	20	50	-	dB
		4800-7000	38	50	-	dB
		7000-11000	-	30	-	dB
		11000-15000	-	20	-	dB



Suggested PCB Layout




HT-LFCG-3000+



50Ω DC to 3000 MHz

Functional Schematic



Pad Connections


INPUT	8
OUTPUT	4
GROUND	1,2,3,5,6,7

Maximum Ratings

Operating Temperature	-55°C to 125°C
Storage Temperature	-55°C to 125°C
RF Power Input*	4.5 W max.@25°C

*Passband rating, derate linearly to 1W at 125°C ambient
Permanent damage may occur if any of these limits are exceeded.

Outline Drawing



Outline Dimensions: Unit ([mm](#))

A	2.00	E	0.30
B	1.25	F	0.30
C	0.95	G	0.65
D	0.35	wt	0.008g