

This document contains proprietary information and such information may not be disclosed to others for any purposes,
not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release	—	H.wei	1/8/14	1/8/14

1 Electrical

- 1.1 Impedance: $50\ \Omega$
- 1.2 Frequency: DC-40GHz
- 1.3 VSWR: 1.20:1
- 1.4 Insertion Loss: 0.3dB max

2 Mechanical&Environmental


- 2.1 Temperature range $-45^{\circ}\text{C} \sim +125^{\circ}\text{C}$
- 2.2 Durability(matings) >500
- 2.3 RoHs Compliant Yes

3 Material&Finish

- 3.1 Pin contact: Beryllium-Copper, gold plated
- 3.2 Body: Stainless Steel(SU303), Passivated
- 3.3 Insulators: PEI

4 Interface Standards

- 4.1 2.92 MIL-STD-348A



Notes:

- 1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
- 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: H.wei 1/8/14	TITLE: Precision Adapter 2.92 Female to 2.92 Female				
ENGINEER: L.yu 1/8/14					
APPROVED: W.yi 1/8/14		 DIMENSION IN MILLIMETERS (mm)			
TOLERANCES UNLESS OTHERWISE SPECIFIED X ± 0.50 .X ± 0.20 .XX ± 0.10 ANGLES $\pm 1^{\circ}$	PART NO: HL-2.92-KKG-F	SIZE: A4	SCALE: N/A	SHEET: 1/1	REV: A