1 2	<u> </u>	3		4	
This document contains proprietary information and such informationmay not be disclosed to others for any purpo	0565	REV DESCRIPTION OF REVISION A Initial Release	ECN NO. BY ————————————————————————————————————	DATE APPROVED	
not used for sales/marketing/procurement purposes without written permission	5553,	A IIIItiai Kelease	II. wei	19/03/17 19/03/17	_
		5			
	\frown				
1 <u>Electrical</u>					A
	/	35	-		
1.1Impedance: 50Ω		<u>flat4</u>			
1.2Frequency:DC-6GHz		<u>ILUI4</u>			
1.3VSWR: 1.20 = 1					
				C I	
2 <u>Environmental</u>				INE	
2.1 Temperature -45° to 125°	/8"-24UNEF-2A			18"-24UNEF	
► 2.2 RoHs compliant	, 			, , , , , , , , , , , , , , , , , , ,	-
3 Material&Finish				<u>L</u>	
3.1 Inner Contact: Phosphor Bronze, gold plated			•		
3.2 Outer Contact: brass, nickel plated					
3.3 Insulators: PTFE		\mathbf{X}			
		\sim			
					В
DRA	WN: H.wei 19/03/17	TITLE:			
Netogy	INEER: L. yu 19/03/17	RF Coaxial Connector		HenryTech	
	ROVED: W.yi 19/03/17	■ N Female to Female ■ Adapter		ENSION IN MILLIMETERS (mm)	
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY	X ±0.50 .X ±0.20 .XX ±0.10	PART NO: HL-N-KKC	SIZE: SCALE:		_
1 2	ANGLES ±1°	2	A4 N/	A SHEET: REV: A	

B