

This document contains proprietary information and such information may not be disclosed to others for any purposes,
not used for sales/marketing/procurement purposes without written permission

REV	DESCRIPTION OF REVISION	ECN NO.	BY	DATE	APPROVED
A	Initial Release	—	H.wei	1/8/14	1/8/14

1 Electrical


- 1.1 Impedance: 50 Ω
- 1.2 Frequency: DC-6GHz
- 1.3 VSWR: 1.20:1

2 Mechanical&Environmental

- 2.1 Temperature range -45°C ~+85°C
- 2.2 Durability(matings) >500
- 2.3 RoHs Compliant Yes

3 Material&Finish

- 3.1 Pin contact: Beryllium-Copper, gold plated
- 3.2 Body: Stainless Steel(SU303), Passivated
- 3.3 Insulators: Teflon



Notes:

- 1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE NOTICE AT ANY TIME
- 2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN : H.wei 1/8/14		TITLE: Precision Adapter SMA Female to U.FL 3 Male				
ENGINEER: L.yu 1/8/14			 DIMENSION IN MILLIMETERS (mm)			
APPROVED : W.yi 1/8/14			PART NO:	HL-SMA-IPEX3-HJG	SIZE: A4	SCALE: N/A
TOLERANCES UNLESS OTHERWISE SPECIFIED					SHEET: 1/1	REV: A
X ±0.50						
.X ±0.20						
.XX ±0.10						
ANGLES ±1°						